Saint Louis University

CHEMICAL HYGIENE PLAN

Prepared by:

Environmental Health and Safety

Saint Louis University
Research Integrity and Safety
Environmental Health and Safety
Caroline Building Suite 305
1402 South Grand Boulevard
St. Louis, Missouri 63104

Reviewed: July 2022

SAINT LOUIS UNIVERSITY

CHEMICAL HYGIENE PLAN

FOR:

_____

(Principal Investigator/Laboratory Manager)

_____

(Building/Room Location)

_____

(Department)

CONTENTS

PURPOSE **5**
POLICY .....

7. HOUSEKEEPING, MAINTENANCE, AND INSPECTIONS 22
A. Housekeeping 22
B. Maintenance 22
C. Inspections 22

8. MEDICAL PROGRAM 24
A. Medical Consultation Determination 24
B. Medical Examinations 24

9. PERSONAL PROTECTIVE EQUIPMENT AND APPAREL 25
A. Types of PPE 25
B. Appropriate Laboratory Apparel 25

10. RECORDS 26

11. SIGNS AND LABELS 27
A. Basic Laboratory Signage 27
B. Refrigerator, Freezer, Cold Room and Microwave Signage 27
C. Hazardous Materials Containers 27

12. SPILLS, ACCIDENTS AND EMERGENCY RESPONSE 28
A. Spills 28
B. Accidents 28
C. Accident Investigation and Reporting 29
D. Emergency Response 29

13. TRAINING 31
A. Chemical Hygiene Plan Training

PURPOSE

All laboratories using hazardous chemicals are required to comply with the Occupational Safety and Health Administration (OSHA)

1. GENERAL PRINCIPLES FOR WORK WITH LABORATORY CHEMICALS

A. Minimize Chemical Exposures

It is prudent to minimize all chemical exposures and observe good laboratory practices by

Providing for the disposal of hazardous chemical waste.
Assisting Facilities Management with incorporating chemical safety in new construction and renovations.
Remaining current on regulatory issues.
Completion of annual and/or semi-annual laboratory safety inspections to ensure safety and regulatory compliance.
Providing Laboratory Safety and Compliance Training to all laboratory employees
Providing disposal requirements and guidelines for both hazardous and non-hazardous chemical waste.
Providing chemical hazard awareness training to ancillary employees.
Conducting exposure assessments as needed, and upon request, for laboratory employees.
Investigating reported workplace injuries from chemical exposures and incidents.

G. Individual Researchers and Laboratory Employees

All new laboratory employees, students, visitors, minors, etc. are required to attend the Saint Louis University Laboratory Safety and Compliance Training prior to working with hazards in a laboratory. Laboratory Safety and Compliance Training is provided by EHS staff on a regular schedule and must be completed at least once during every twelve-month period. In

3. LABORATORY FACILITY

A. Design

Saint Louis University laboratories in which hazardous chemicals are present or used shall have the following minimum safety features within the immediate area or close proximity:

An appropriate general ventilation system with air intakes and exhausts located so as to avoid intake of contaminated air.
Adequate, well ventilated stockrooms/storerooms.
Local exhaust ventilation for chemical usage (laboratory fume hoods).
Chemical storage areas and cabinets.
Laboratory sinks.
Safety showers and eye washes.
Fire extinguishers.

B. Maintenance

The Facilities Management Department ensures that laboratory safety systems are maintained in a serviceable condition, according to the manufacturer's specifications. Fire extinguishers are maintained under the management of EHS and Facilities Management. Work orders to repair or renovate laboratory facilities may be initiated by principal investigators, laboratory employees, EHS or Facilities Management staff.

C. Usage

Work conducted in Saint Louis University laboratories is for research or instructional purposes. Work is laboratory scale in nature, and activities are conducted appropriate to the physical limitations of the laboratory facilities and safety equipment available, and especially appropriate to the quality of ventilation, including local exhaust systems. EHS

Laboratory Fume Hoods

Laboratory fume hoods shall be provided, installed and operated according to manufacturer specifications.

When the hood sash is open approximately twelve inches, an average face velocity of

4. BASIC RULES AND PROCEDURES FOR WORKING WITH CHEMICALS

A. General Principles

This Chemical Hygiene Plan requires that laboratory workers understand and follow basic procedures for working with chemicals. *Prudent Practices for Handling Hazardous Chemicals in Laboratories* may be used as a supplemental reference. The general principles listed below should be used for all laboratory work with chemicals.

1. Accidents and Spills

Know the appropriate emergency response procedures.
In the event of an accidental eye exposure, promptly flush the eyes with water for a prolonged period (15 minutes) and seek medical attention.
After ingestion of a hazardous substance, e

6. Exiting

Wash areas of exposed skin thoroughly with soap and water before leaving the laboratory.

7. Horseplay

Avoid distracting or startling other workers when they are handling hazardous chemicals.

8. Mouth Suction/Mouth Pipetting

Do not use mouth suction for pipetting or starting a siphon.

9. Personal Housekeeping

Keep the work area clean and uncluttered, with chemicals and equipment properly labeled and stored.

Clean up the work area on completion of an operation and/or at the end of each day.

10. Personal Protection

Wear adequate eye, face, hand and foot protection when working with chemicals or other hazards in the laboratory.

Assure that appropriate eye protection is worn by all persons, including visitors, where chemicals are in use or handled.

Wear appropriate gloves when the potential for contact with hazardous materials exists and remember to inspect gloves before each use.

Wear closed-toed shoes at all times in the laboratory.

Use appropriate respiratory protective equipment when air contaminant concentrations cannot be adequately managed by engineering controls, inspecting the respirator before each use.

13. Vigilance

Always be alert to unsafe conditions and actions and call attention to them so that corrective action can be taken as quickly as possible.

14. Waste Disposal

Follow established University chemical waste disposal procedures in accordance with guidance and requirements provided by EHS.

Do not discharge to the sewer concentrated acids or bases; highly toxic,

Safety and Emergency Preparedness (DPSEP) of all incidents of exposure or spills. Consult the Employee Health physician or another qualified physician when appropriate.

D. Working with Chemicals of Moderate Chronic or High Acute Toxicity

Any intended use or possession of chemicals of moderate chronic or high acute toxicity must be reported to EHS prior to use. Examples of chemicals of moderate chronic or high acute toxicity include, but are not limited to, diisopropyl fluorophosphate, hydrofluoric acid, and hydrogen cyanide. Supplemental rules to be followed in addition to those mentioned above include:

1. Preparation:

Report the presence and intended use of these chemicals to EHS prior to initial use.

Develop and document adequate training of all employees working with or in the presence of these chemicals.

Minimize exposure to these toxic substances by any route using all reasonable precautions.

2. Location and Engineering Controls:

Use and store these substances only in areas of restricted access with special warning signs.

Always use a fume hood confirmed to exhibit adequate performance with a face velocity of at least 100 ft/min or other containment device (e.g. glove box or specially designed exhaust system), for procedures which may result in the generation of aerosols or vapors containing the substance.

Trap released vapors to prevent their discharge by the fume hood exhaust.

3. Personal Protective Equipment and Practices:

Always avoid skin contact by use of gloves and sleeve coverings (and other protective apparel as appropriate).

Always wash hands and arms immediately after working with these materials.

4. Prevention of Spa 373.63 Tm0 g0 G[2(c)2BT/F8v0 61(Ac8(C q0.00000912 0 612 792 reW*nB

E. Working with Chemicals of High Chronic Toxicity

Any intended use or possession of chemicals of high chronic toxicity must be reported to EHS prior to use. Examples of chemicals of high chronic toxicity include, but are not limited to, dimethylmercury, nickel carbonyl, benzo-a-pyrene, N-nitrosodiethylamine, and other human carcinogens or substances with high carcinogenic potency in animals.

Further supplemental rules to be followed in addition to all those mentioned above, for work with substances of known high chronic toxicity (in quantities above a few milligrams to a few grams, depending on the substance) include:

1. **Preparation:**

   Report the presence and intended use of these chemicals to EHS prior to initial use.

   Develop and document adequate training of all employees working with or in the presence of these chemicals.

   Prepare a plan for use and disposal of these materials and obtain the approval of the laboratory supervisor and Chemical Hygiene Officer.

2. **Location and Engineering Controls:**

   Conduct all transfers and work with these substances in a "controlled area" such as a restricted access hood, glove box, or portion of a lab designated for use of highly toxic substances for which all people with access are aware of the substances being used and all necessary precautions.

   For a negative pressure glove box, the ventilation rate must be at least 2 volume

5. CHEMICAL PROCUREMENT, DISTRIBUTION AND STORAGE

A. Procurement of Chemicals

No chemical container shall be accepted without an adequate identifying label and delivery should be refused for any leaking containers. In order to minimize the presence of hazardous materials at the University, chemicals should be ordered in the smallest quantity needed to conduct the work. Limit the purchase of hazardous chemicals to containers equal to or less than five gallons each and consider using chemical from stocks already on campus. EHS shall be contacted in advance of any acquisition of chemicals that will not be purchased but donated or transferred to Saint Louis University from another institution, individual or organization.

B. Stockrooms/Storerooms

Hazardous substances should be segregated by hazard class, following manufacturer

Housekeeping and chemical hygiene inspections are recommended and should be routinely conducted by the principal investigator, laboratory manager, or appointed representative. Use of the Environmental Safety Laboratory Inspection Form is encouraged unless the laboratory PI or staff design a checklist specific to their laboratories.

8. MEDICAL PROGRAM

A. Medical Consultation Determination

Medical consultations will be provided by Employee Health, upon request, to employees exposed to hazardous chemicals as a result of a spill, leak or explosion. The licensed Employee Health physician performing the initial consultation will identify the need for further medical examinations. Medical consultations will be required for documented exposures above established action levels or airborne concentrations above the PEL, TLV, or other recognized exposure limit and for any employee exhibiting signs or symptoms consistent with exposure to the chemicals with which they are working.

B. Medical Examinations

The medical exam criteria will be determined by the Employee Health physician. Where medical exam guidance exists, such as, for OSHA regulated substances, these criteria will be included in the physician's exam. For examinations resulting from

9. PERSONAL PROTECTIVE EQUIPMENT AND APPAREL

Personal protective equipment (PPE) is a term used to describe a variety of products worn by laboratory employees designed to protect those employees from safety and health hazards. Protective equipment is required anytime there is a possibility that the employee may be exposed to a hazardous chemical. The level of protection required depends on the specific hazards involved and the manner in which the material or materials are handled.

5. **Gloves:** Wear appropriate gloves when the potential for contact with hazardous materials exists. Inspect the gloves before each use and replace them periodically. Gloves should not be worn outside of the laboratory. Disposable gloves should never be reused.
6. **Shoes:** Closed-toed shoes shall always be worn in laboratories to reduce the risk of injury to feet from spills, broken glass, or objects dropped in the laboratory.
7. **Pants:** Shorts should not be worn in the laboratory. Loose fitting long pants provide the best protection against accidental splashes. Legs should be covered entirely to the ankles.
8. **Shirts:** Shirts or tops should cover the entire midsection and easily accommodate a lab coat.

10. RECORDS

The Saint Louis University Risk Management and Insurance Department maintains all university illness and accident reports. Employee Health maintains all medical records relating to all reported chemical exposures and potential chemical exposures. EHS maintains all laboratory safety inspections, chemical fume hood certification records and all radiation dosimetry records.

11. SIGNS AND LABELS

A. Basic Laboratory Signage

The following signs shall be prominently posted:

Emergency telephone numbers (posted near the phone).

Location signs for safety showers, eye washes, fire extinguishers, and first aid equipment.

Warning signs at areas or equipment where special or unusual hazards exist.

Laboratory entry hazard warning signs with emergency contact numbers.

B. Refrigerator, Freezer, Cold Room and Microwave Signage

All standard laboratory refrigerators, freezers, cold rooms and microwaves used for chemical storage or preparation must have the following labels clearly posted:

NOT FOR FOOD OR DRINK

DO NOT STORE FLAMMABLES/SOLVENTS IN THIS REFRIGERATOR/ FREEZER

C. Hazardous Materials Containers

The following rules for hazardous materials containers shall be followed:

Labels on incoming containers of hazardous chemicals are not to be removed or defaced until the container is empty and triple rinsed.

Secondary use containers (containers used for dispensing from bulk containers or containers of chemical mixtures prepared in the lab) should be labeled with complete chemical name, concentration, and the hazard class.

12. SPILLS, ACCIDENTS AND EMERGENCY RESPONSE

A. Spills

Occasionally, and in spite of our best efforts to prevent them, accidents will occur in the laboratory. The most common accident in the laboratory is a chemical spill. For this reason, Saint Louis University has a Hazmat Response Team that is on call 24 hours a day, 7 days a week. This team is managed by EHS and can be reached by calling the Department of Public Safety and Emergency Preparedness (DPSEP) at 314-977-3000.

The following procedures should be followed in the event of a chemical spill in your laboratory:

Personnel Decontamination: In the event of skin or eye exposure to a chemical, immediately flush the area with water for 15 minutes.

Evacuate the immediate area of the spill and adjacent areas.

Notify your supervisor and/or other employees in the area.

Contact DPSEP at 314-977-3000 to report the spill and request assistance.

1. State that you have had a chemical spill.
2. Provide DPSEP with:
    a. correct spelling of the chemical name
    b. volume of chemical spilled
    c. exact location of the spill, including building name and room number
    d. contact phone number at which you can receive a return phone call

Seek medical attention from the SSM Health Saint Louis University Hospital Emergency Department or Employee Health, if necessary. All injuries/illnesses should be reported on the Employee Report of Injury form.

B. Accidents

Accidents involving fire or explosions will activate installed automatic alarm sensors and fire extinguishing systems. Where automatic systems do not exist, manual alarm pull stations are installed along egress routes and must be activated during evacuation.

Accidents involving hazardous chemical spills, fires, or explosions shall be immediately reported to Saint Louis University Department of Public Safety and Emergency Preparedness at 314-977-3000. DPSEP will contact the approp TJn130.5reW*ntETQq0.000

2.

30

13. TRAINING

4. **Inadequate Labels:** Labels such as "Inorganic Waste" and "Organic Solvent Waste" are not adequate and would require listing of individual chemical components. Abbreviations can be ambiguous, and are not allowed. The identity of a waste container's contents must be unmistakable.
5. **Defacing of Original Labels**: Any original/existing labels must be defaced by either removal or clearly marking through the original label if or when the container is empty.

D.

15. SAFETY DATA SHEET (SDS)

The Occupational Safety and Health Administration (OSHA) requires all chemical manufacturers, wholesalers, and distributors to provide Safety Data Sheets (SDS) for the products which they produce and sell. OSHA also requires that employers maintain in the workplace, copies of the SDS for each hazardous chemical. SDS are required to be accessible at all times work is being conducted. With any chemical, it is prudent to consult the SDS before use. In general, a SDS consists of the following sections:

1. Chemical Identification
2. Hazards Identification
3. Composition/Information on Ingredients
4. First-Aid Measures
5. Fire-Fighting Measures
6. Accidental Release Measures
7. Handling and Storage
8. Exposure Controls and Personal Protection
9. Physical/ Chemical Properties
10. Stability and Reactivity
11. Toxicological Information
12. Ecological Information
13. Disposal Considerations
14. Transport Information
15. Regulatory Information

Typically, SDS are shipped with the chemical order or you may contact the manufacturer to request the SDS. EHS maintains a SDS collection as a resource to all Saint Louis University employees, students and visitors.